



Data Center – Products & Solutions



Deep-Dive: ParaLink® - High speed data cables

For data center cabling

- › For transmission of signals in data centers with speeds up to 100 Gbit/s per channel (PAM4)
- › Parallel pairs (Twinax), separately shielded
- › Available in different jacket materials, e.g. flame retardant PVC and halogen free
- › Various construction options, e.g.
 - › AWG sizes 26 to 32
 - › Number of pairs 1 to 24
 - › Hybrid solutions
- › LEONizell® dielectric
- › VDE, UL and CSA approval



Deep-Dive: High Speed Cable Assemblies & Loopback Test Adapters

For data center cabling



- › Direct Attach copper cables, e.g.
 - › SFP+, SFP28
 - › QSFP+, QSFP28
 - › QSFP-DD, OSFP
- › Breakout cable systems, e.g.
 - › Q-4S (QSFP+ on 4xSFP+, QSFP28 to 4 x SFP28)
 - › Q-2Q (QSFP28 on 2xQSFP28)
 - › Customised solutions involving cables & breakouts
 - › QDD-2Q, QDD-4Q, QDD-8S
 - › ODD-2Q, ODD-4Q, ODD-8S



- › Available for form factors: SFP, QSFP, QSFP-DD, OSFP
- › Diagnostic functions via LED (temperature, voltage/load)
- › Different pull-tab color options
- › Extended plug cycles due to special contact surface
- › Operates in temperature range from 0°C to 70°C (SFP), up to 125°C (QSFP) and up to 85°C (QSFP-DD / OSFP)

5G Mobile Telecom

Core & Mobile Networks – Products & Solutions

IP68-tight jumper cables

UV resistant data cables

Hybrid FTTH cables incl. fiber and copper

Standard and customised coax cables

Tomorrow:
Smart solutions including sensor equipped connections and predictive analytics

Today:
Wide range of cables for various telecommunication applications in- & outdoors